

Korenix Industrial Product Selection Guide - Serial Device Server



Redundant Serial Server Isolation Redundant Serial Server Redundant Serial Server Fiber Serial Server Wireless Device Server Serial Server

Interface						
Number of Ports:10/100Base-TX	2(Redundant)	2(Redundant)	2(Redundant)		1	1
Number of Ports: WLAN					1	
Number of Ports:100Base-FX (Multi Mode Fiber)				1		
(Single Mode Fiber)				JetPort 5601f-m		
				JetPort 5601f-s		
Number of Serial Ports	4*RS232/422/485	4*RS422/485 with 2KV Isolation	1* RS232/422/485	1* RS232/422/485	1* RS232/ 422/485	1* RS232
Power Terminal	DC12~48V	DC12~48V	DC12~48V	DC12~48V	DC12~48V	
Power Jack	DC12~48V	DC12~48V	DC9~30V	DC9~30V	DC12~48V	DC9~30V
Fault Relay Output	4 Digital Inputs 2 Digital Outputs	4 Digital Inputs 2 Digital Outputs				
1200VAC HIPOT	●	●	●	●	●	●
Mechanical						
Rigid Aluminum Case	●	●	●	●	●	●
Dimensions (unit=mm)	145(W) x 46.5(H) x 120(D)	145(W) x 46.5(H) x 120(D)	96.1(W) x 29.6(H) x 99(D)		96.1(W) x 29.6(H) x 124(D)	78.5(W)x29.2(H) x 79.6(D)
Case Protection	IP 30	IP 30	IP 30	IP 30	IP 30	IP 30
Operating Temperature	-10~70°C	-10~70°C	-10~70°C	-10~70°C	-10~55°C	0~60°C
DIN-Rail Kit	●	●	●	●	●	●
Protocols						
Web-based Configuration	●	●	●	●	●	●
Windows Utility	●	●	●	●	●	●
Secured HTTPS,SSH	●	●	●	●	●	
Super Ring, Couple Ring, Dual Homing						
RTTD, Redundant Dual Ethernet	●	●	●			
IGMP Snooping						
Port VLAN						
Quality of Service						
SNMP V1/V2C	●	●	●	●	●	●
RMON1						
SMTP(e-mail warning)	●	●	●	●	●	●
Syslog	●	●	●	●	●	●
Certifications						
Regulatory Approvals:CE / FCC / UL	●	●	●	●	●	●
RoHS / WEEE	●	●	●	●	●	●