

JetWave 2212X

Basic Industrial Wireless AP/Client

- 802.11 a/b/g/n 2.4G/5G Band
- 2T2R MIMO doubles data rate up to 300Mbps
- Dual Fast Ethernet
- Dual 24V(9~26V) DC Redundant
- 1 x Digital input design



JetWave 2212S

Serial Industrial Wireless AP/Client

- 802.11 a/b/g/n 2.4G/5G Band
- 2T2R MIMO doubles data rate up to 300Mbps
- Dual Fast Ethernet
- 2 ports RS232/422/485 3 in 1
- Dual 24V(9~26V) DC Redundant
- 1 x Digital input design



JetWave 2212G

High Speed Industrial Wireless AP/Client

- 802.11 a/b/g/n/ac 2.4G/5G Band
- 2T2R MIMO doubles data rate up to 867Mbps per radio
- Dual Gigabit Ethernet
- Dual 24V(12~48V) DC Redundant
- 1 x Digital input design
- Passive PoE 24/48VDC



JetWave 3220 V3

Dual Radio 2.4G/5G Wireless AP/Client

- 802.11 a/b/g/n/ac and 2.4G/5G Band
- 2T2R MIMO doubles data rate up to 866Mbps per radio
- Dual Gigabit Ethernet
- Dual 24V(12~48V) DC Redundant
- IEEE802.3at PoE (PD)
- DI + DO



JetWave 3420 V2

LTE plus 802.11ac WIFI Wireless IP Gateway

- 2x2 DL-MIMO, max. 100MDL/50MUL
- 802.11 a/b/g/n/ac and 2.4G/5G Band
- Dual Gigabit Ethernet
- LAN/WIFI to LTE Cellular Routing
- Supports RS-232/422/485 Serial port
- Dual 24V(12~48V) DC Redundant
- IEEE802.3at PoE (PD)
- DI + DO



JetWave 2714GF-WiFi

High Speed Industrial Wireless AP/Switch

- 802.11 a/b/g/n/ac 2.4G/5G Band
- 2T2R MIMO doubles data rate up to 866Mbps per radio
- 2GT PSE + 2G SFP Gigabit PoE Switch
- Dual Gigabit Ethernet
- Dual 48V(48~54V) DC Redundant
- 1 x Digital input design



Outdoor

JetWave 4020(E)

Outdoor Wireless AP

- Industry leading 802.11ac WIFI
- Dual Band Dual Radio
- Dual M12 Gigabit Ethernet
- M12 24V/110VDC Power Input
- Passive PoE 24VDC
- IP67 Waterproof, -40~70°C operating temperature
- "E" external antenna model



JetWave 2450 V2

Outdoor Wireless AP

- 802.11n 2T2R MIMO data rate up to 300Mbps
- Internal 9dBi directional antenna (Vertical 60°, Horizontal 70°)
- Passive PoE 24VDC
- IP55, -20~70°C operating temperature



Industrial Cellular Product

JetWave 2111

Basic Industrial Cellular Router/Gateway

- (LTE Cat 1) technology, DL-MIMO, max. 10M DL/5M UL
- One MicroSD card slot support
- 1 DI + 1 DO
- 1 port RS232/422/485 3 in 1 (RJ45 type)
- 1 Fast Ethernet Port
- 24V(9~30V) DC power input
- Support GPS (Optional)
- Single SIM card



JetWave 2411

Basic Industrial Cellular Router/Gateway

- (LTE Cat 4) technology, DL-MIMO, max. 150M DL/50M UL
- One MicroSD card slot support
- 1 DI + 1 DO
- 1 port RS232/422/485 3 in 1 (RJ45 type)
- 1 Fast Ethernet Port
- 24V(9~30V) DC power input
- Support GPS (Optional)
- Single SIM card



JetWave 2114

Industrial Cellular Router/Gateway

- (LTE Cat 1) technology, DL-MIMO, max. 10M DL/5M UL
- One MicroSD card slot support
- 2 DI + 2 DO
- 2 ports RS232/422/485 3 in 1 (RJ45 type)
- 4 Fast Ethernet Port
- 24V(9~48V) DC power input
- Support GPS (Optional)
- Dual SIM Redundant
- Passive PoE 24/48VDC



JetWave 2414

Industrial Cellular Router/Gateway

- (LTE Cat 4) technology, DL-MIMO, max. 150M DL/50M UL
- One MicroSD card slot support
- 2 DI + 2 DO
- 2 ports RS232/422/485 3 in 1 (RJ45 type)
- 4 Fast Ethernet Port
- 24V(9~48V) DC power input
- Support GPS (Optional)
- Dual SIM Redundant
- Passive PoE 24/48VD



JetWave 3420 V2

LTE plus 802.11ac WIFI Wireless IP Gateway

- 2x2 DL-MIMO, max. 100MDL/50MUL
- 802.11 a/b/g/n/ac and 2.4G/5G Band
- Dual Gigabit Ethernet
- LAN/WIFI to LTE Cellular Routing
- Supports RS-232/422/485 Serial port
- Dual 24V(12~48V) DC Redundant
- IEEE802.3at PoE (PD)
- DI + DO
- Dual SIM Redundant



JetWave 2714GF-LTE

High Speed Industrial Wireless Router/Switch

- LTE 2x2 DL-MIMO, max. 100MDL/50M UL
- Dual SIM Redundant
- 2GT PSE + 2G SFP Gigabit PoE Switch
- Dual Gigabit Ethernet
- Dual 48V(48~54V) DC Redundant
- 1 x Digital input design



Korenix Technology Co., Ltd

www.korenix.com

Tel: +886 2 8911 1000

Fax: +886 2 2912 3328

Business: sales@korenix.com

Service: korecare@korenix.com

