

| Type        | Model Name       | Des.   | Speed |   |     | BIDI | Wave Length |      | Distance | Temp.    | DDM | Warranty |
|-------------|------------------|--|-------|---|-----|------|-------------|------|----------|----------|-----|----------|
|             |                  |  | 100   | G | 10G |      | TX          | RX   |          |          |     |          |
| Multi-Mode  | SFP10GSRD        | [SFP10GSRD] Multi-mode 10Gbps 300M(OM3) Fiber Transceiver with DDMI, LC, Operating Temp. -10~70°C        |       |   | V   |      | 850         | 850  | 300M     | -10~70°C | V   | 1        |
| Multi-Mode  | SFPGSXB813       | [SFPGSXB813] SFP Transceiver, 1.25 Gigabit, TX-1310/RX-1550, Multi-mode, BIDI, 500m, LC, Temp. 0°C~70°C  |       | V |     | V    | 1310        | 1550 | 500M     | 0~70°C   |     | 1        |
| Multi-Mode  | SFPGSXB815       | [SFPGSXB815] SFP Transceiver, 1.25 Gigabit, TX-1550/RX-1310, Multi-mode, BIDI, 500m, LC, Temp. 0°C~70°C  |       | V |     | V    | 1550        | 1310 | 500M     | 0~70°C   |     | 1        |
| Multi-Mode  | SFPGSX           | [SFPGSX] 1000Base-SX Multi-mode Transceiver 550m, LC, Operating Temp. -10~70°C                           |       | V |     |      | 850         | 850  | 550M     | -10~70°C |     | 1        |
| Multi-Mode  | SFPGSX-w         | [SFPGSX-w] 1000Base-SX Multi-mode Transceiver 550m, LC, Operating Temp. -40~85°C                         |       | V |     |      | 850         | 850  | 550M     | -40~85°C |     | 1        |
| Multi-Mode  | SFPGXD           | [SFPGXD] 1000Base-SX Multi-mode Transceiver 550m w/ DDMI, LC, Operating Temp. -10~70°C                   |       | V |     |      | 850         | 850  | 550M     | -10~70°C | V   | 1        |
| Multi-Mode  | SFPGXD-w         | [SFPGXD-w] 1000Base-SX Multi-mode Transceiver 550m w/ DDMI, LC, Operating Temp. -40~85°C                 |       | V |     |      | 850         | 850  | 550M     | -40~85°C | V   | 1        |
| Multi-Mode  | SFP100MM         | [SFP100MM] Multi-mode 100Mbps 2KM Fiber Transceiver, LC, Operating Temp. -10~70°C                        | V     |   |     |      | 1310        | 1310 | 2KM      | -10~70°C |     | 1        |
| Multi-Mode  | SFP100MM-w       | [SFP100MM-w] Multi-mode 100Mbps 2KM Fiber Transceiver, LC, Wide Operating Temp. -40~85°C                 | V     |   |     |      | 1310        | 1310 | 2KM      | -40~85°C |     | 1        |
| Multi-Mode  | SFP100MMD        | [SFP100MMD] Multi-mode 100Mbps 2KM Fiber Transceiver with DDMI, LC, Operating Temp. -10~70°C             | V     |   |     |      | 1310        | 1310 | 2KM      | -10~70°C | V   | 1        |
| Multi-Mode  | SFP100MMD-w      | [SFP100MMD-w] Multi-mode 100Mbps 2KM Fiber Transceiver with DDMI, LC, Operating Temp. -40~85°C           | V     |   |     |      | 1310        | 1310 | 2KM      | -40~85°C | V   | 1        |
| Multi-Mode  | SFPGX2           | [SFPGX2] Multi-mode 1000Base-SX 2KM Fiber Transceiver, LC, -10~70°C                                      |       | V |     |      | 1310        | 1310 | 2KM      | -10~70°C |     | 1        |
| Multi-Mode  | SFPGX2-w         | [SFPGX2-w] 1000Base-SX Multi-mode Transceiver 2km, LC, Operating Temp. -40~85°C                          |       | V |     |      | 1310        | 1310 | 2KM      | -40~85°C |     | 1        |
| Multi-Mode  | SFPGX2D          | [SFPGX2D] 1000Base-SX Multi-mode Transceiver 2km w/ DDMI, LC, Operating Temp. -10~70°C                   |       | V |     |      | 1310        | 1310 | 2KM      | -10~70°C | V   | 1        |
| Multi-Mode  | SFPGX2D-w        | [SFPGX2D-w] 1000Base-SX Multi-mode Transceiver 2km w/ DDMI, LC, Operating Temp. -40~85°C                 |       | V |     |      | 1310        | 1310 | 2KM      | -40~85°C | V   | 1        |
| Multi-Mode  | SFP100MM5        | [SFP100MM5] Multi-mode 100Mbps 5KM Fiber Transceiver w/ LC, Temp. -10°C~70°C                             | V     |   |     |      | 1310        | 1310 | 5KM      | 0~70°C   |     | 1        |
| Multi-Mode  | SFP100MM5-w      | [SFP100MM5-w] Multi-mode 100Mbps 5KM Fiber Transceiver w/ LC, Temp. -40°C~85°C                           | V     |   |     |      | 1310        | 1310 | 5KM      | -40~85°C |     | 1        |
| Multi-Mode  | SFP100MM5D       | [SFP100MM5D] SFP-100Mbps, 125Mbps, 1310nm, Multi-mode, 5km, 0~70°C, LC with DDM function                 | V     |   |     |      | 1310        | 1310 | 5KM      | 0~70°C   | V   | 1        |
| Multi-Mode  | SFP100MM5D-w     | [SFP100MM5D-w] SFP-100Mbps, 125Mbps, 1310nm, Multi-mode, 5km, -40~85°C, LC with DDM function             | V     |   |     |      | 1310        | 1310 | 5KM      | -40~85°C | V   | 1        |
| Single Mode | SFPLGX10         | [SFPLGX10] Single-mode 1000Base-LX 10KM Fiber Transceiver, LC, -10~70°C                                  |       | V |     |      | 1310        | 1310 | 10KM     | -10~70°C |     | 1        |
| Single Mode | SFPLGX10-w       | [SFPLGX10-w] 1000Base-LX Single-mode Transceiver 10km, LC, Operating Temp. -40~85°C                      |       | V |     |      | 1310        | 1310 | 10KM     | -40~85°C |     | 1        |
| Single Mode | SFPLGX10D        | [SFPLGX10D] 1000Base-LX Single-mode Transceiver 10km w/ DDMI, LC, Operating Temp. -10~70°C               |       | V |     |      | 1310        | 1310 | 10KM     | -10~70°C | V   | 1        |
| Single Mode | SFPLGX10D-w      | [SFPLGX10D-w] 1000Base-LX Single-mode Transceiver 10km w/ DDMI, LC, Operating Temp. -40~85°C             |       | V |     |      | 1310        | 1310 | 10KM     | -40~85°C | V   | 1        |
| Single Mode | SFPLGX10B13      | [SFPLGX10B13] 1000Base-LX, S.M., BIDI TX 1310/RX 1550nm, 10Km, LC, Temp. -10°C~70°C                      |       | V |     | V    | 1310        | 1550 | 10KM     | -10~70°C |     | 1        |
| Single Mode | SFPLGX10B15      | [SFPLGX10B15] 1000Base-LX, S.M., BIDI TX 1550/RX 1310nm, 10Km, LC, Temp. -10°C~70°C                      |       | V |     | V    | 1550        | 1310 | 10KM     | -10~70°C |     | 1        |
| Single Mode | SFPLGX10B13-w    | [SFPLGX10B13-w] Single-mode 1000Base-LX 10KM Fiber Transceiver, BIDI/WDM TX 1310/RX 1550nm, LC, -40~85°C |       | V |     | V    | 1310        | 1550 | 10KM     | -40~85°C |     | 1        |
| Single Mode | SFPLGX10B15-w    | [SFPLGX10B15-w] Single-mode 1000Base-LX 10KM Fiber Transceiver, BIDI/WDM TX 1550/RX 1310nm, LC, -40~85°C |       | V |     | V    | 1550        | 1310 | 10KM     | -40~85°C |     | 1        |
| Single Mode | SFPLGX10B13D     | [SFPLGX10B13D] 1000Base-LX, S.M., BIDI DDM TX 1310/RX 1550nm, 10km, LC, Temp. -10°C~70°C                 |       | V |     | V    | 1310        | 1550 | 10KM     | -10~70°C | V   | 1        |
| Single Mode | SFPLGX10B15D     | [SFPLGX10B15D] 1000Base-LX, S.M., BIDI DDM TX 1550/RX 1310nm, 10km, LC, Temp. -10°C~70°C                 |       | V |     | V    | 1550        | 1310 | 10KM     | -10~70°C | V   | 1        |
| Single Mode | SFPLGX10B13D-w   | [SFPLGX10B13D-w] 1000Base-LX, S.M., BIDI DDM TX 1310/RX 1550nm, 10km, LC, Temp. -40~85°C                 |       | V |     | V    | 1310        | 1550 | 10KM     | -40~85°C | V   | 1        |
| Single Mode | SFPLGX10B15D-w   | [SFPLGX10B15D-w] 1000Base-LX, S.M., BIDI DDM TX 1550/RX 1310nm, 10km, LC, Temp. -40~85°C                 |       | V |     | V    | 1550        | 1310 | 10KM     | -40~85°C | V   | 1        |
| Single Mode | SFP10GLR10D      | [SFP10GLR10D] Single-mode 10Gbps 10KM Fiber Transceiver with DDM, LC, Operating Temp. -10~70°C           |       |   | V   |      | 1310        | 1310 | 10KM     | -10~70°C | V   | 1        |
| Single Mode | SFP100SM20B13    | [SFP100SM20B13] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 20Km, LC, Temp. -10°C~70°C                | V     |   |     | V    | 1310        | 1550 | 20KM     | -10~70°C |     | 1        |
| Single Mode | SFP100SM20B15    | [SFP100SM20B15] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 20Km, LC, Temp. -10°C~70°C                | V     |   |     | V    | 1550        | 1310 | 20KM     | -10~70°C |     | 1        |
| Single Mode | SFP100SM20B13-w  | [SFP100SM20B13-w] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 20Km, LC, Temp. -40°C~85°C              | V     |   |     | V    | 1310        | 1550 | 20KM     | -40~85°C |     | 1        |
| Single Mode | SFP100SM20B15-w  | [SFP100SM20B15-w] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 20Km, LC, Temp. -40°C~85°C              | V     |   |     | V    | 1550        | 1310 | 20KM     | -40~85°C |     | 1        |
| Single Mode | SFP100SM20B13D   | [SFP100SM20B13D] 100Mbps BIDI DDM single-mode transceiver 1310nm 20km                                    | V     |   |     | V    | 1310        | 1550 | 20KM     | -10~70°C | V   | 1        |
| Single Mode | SFP100SM20B15D   | [SFP100SM20B15D] 100Mbps BIDI DDM single-mode transceiver 1550nm 20km                                    | V     |   |     | V    | 1550        | 1310 | 20KM     | -10~70°C | V   | 1        |
| Single Mode | SFP100SM20B13D-w | [SFP100SM20B13D-w] 100Mbps BIDI DDM single-mode transceiver 1310nm 20km, -40°C~85°C                      | V     |   |     | V    | 1310        | 1550 | 20KM     | -40~85°C | V   | 1        |
| Single Mode | SFP100SM20B15D-w | [SFP100SM20B15D-w] 100Mbps BIDI DDM single-mode transceiver 1550nm 20km, -40°C~85°C                      | V     |   |     | V    | 1550        | 1310 | 20KM     | -40~85°C | V   | 1        |
| Single Mode | SFPLGX20B13      | [SFPLGX20B13] 1000Base-LX, S.M., BIDI TX 1310/RX 1550nm, 20Km, LC, Temp. -10°C~70°C                      |       | V |     | V    | 1310        | 1550 | 20KM     | -10~70°C |     | 1        |
| Single Mode | SFPLGX20B15      | [SFPLGX20B15] 1000Base-LX, S.M., BIDI TX 1550/RX 1310nm, 20Km, LC, Temp. -10°C~70°C                      |       | V |     | V    | 1550        | 1310 | 20KM     | -10~70°C |     | 1        |
| Single Mode | SFPLGX20B13-w    | [SFPLGX20B13-w] 1000Base-LX, S.M., BIDI TX 1310/RX 1550nm, 20Km, LC, Temp. -40°C~85°C                    |       | V |     | V    | 1310        | 1550 | 20KM     | -40~85°C |     | 1        |
| Single Mode | SFPLGX20B15-w    | [SFPLGX20B15-w] 1000Base-LX, S.M., BIDI TX 1550/RX 1310nm, 20Km, LC, Temp. -40°C~85°C                    |       | V |     | V    | 1550        | 1310 | 20KM     | -40~85°C |     | 1        |
| Single Mode | SFPLGX20B13D     | [SFPLGX20B13D] 1000Base-LX, S.M., BIDI DDM TX 1310/RX 1550nm, 20km, LC, Temp. -10°C~70°C                 |       | V |     | V    | 1310        | 1550 | 20KM     | -10~70°C | V   | 1        |
| Single Mode | SFPLGX20B15D     | [SFPLGX20B15D] 1000Base-LX, S.M., BIDI DDM TX 1550/RX 1310nm, 20km, LC, Temp. -10°C~70°C                 |       | V |     | V    | 1550        | 1310 | 20KM     | -10~70°C | V   | 1        |
| Single Mode | SFPLGX20B13D-w   | [SFPLGX20B13D-w] 1000Base-LX, S.M., BIDI DDM TX 1310/RX 1550nm, 20km, LC, Temp. -40°C~85°C               |       | V |     | V    | 1310        | 1550 | 20KM     | -40~85°C | V   | 1        |
| Single Mode | SFPLGX20B15D-w   | [SFPLGX20B15D-w] 1000Base-LX, S.M., BIDI DDM TX 1550/RX 1310nm, 20km, LC, Temp. -40°C~85°C               |       | V |     | V    | 1550        | 1310 | 20KM     | -40~85°C | V   | 1        |
| Single Mode | SFP10GLR20D      | [SFP10GLR20D] Single-mode 10Gbps 20KM Fiber Transceiver with DDM, LC, Operating Temp. -10~70°C           |       |   | V   |      | 1310        | 1310 | 20KM     | -10~70°C | V   | 1        |
| Single Mode | SFP100SM30       | [SFP100SM30] Single-mode 100Mbps 30KM Fiber Transceiver, LC, Operating Temp. -10~70°C                    | V     |   |     |      | 1310        | 1310 | 30KM     | -10~70°C |     | 1        |
| Single Mode | SFP100SM30-w     | [SFP100SM30-w] 100Base-FX Single-mode Transceiver 30KM, LC, Industrial Operating Temp. -40~85°C          | V     |   |     |      | 1310        | 1310 | 30KM     | -40~85°C |     | 1        |
| Single Mode | SFP100SM30D      | [SFP100SM30D] Single-mode 100Mbps 30KM Fiber Transceiver with DDMI, LC, Operating Temp. -10~70°C         | V     |   |     |      | 1310        | 1310 | 30KM     | -10~70°C | V   | 1        |
| Single Mode | SFP100SM30D-w    | [SFP100SM30D-w] Single-mode 100Mbps 30KM Fiber Transceiver with DDMI, LC, Operating Temp. -40~85°C       | V     |   |     |      | 1310        | 1310 | 30KM     | -40~85°C | V   | 1        |
| Single Mode | SFPLHX30         | [SFPLHX30] 1000Base-LHX Single-mode Transceiver 30km, LC, Operating Temp. -10~70°C                       |       | V |     |      | 1310        | 1310 | 30KM     | -10~70°C |     | 1        |
| Single Mode | SFPLHX30-w       | [SFPLHX30-w] 1000Base-LHX Single-mode Transceiver 30km, LC, Operating Temp. -40~85°C                     |       | V |     |      | 1310        | 1310 | 30KM     | -40~85°C |     | 1        |
| Single Mode | SFPLHX30D        | [SFPLHX30D] 1000Base LHX DDM single-mode transceiver 30km, -10°C~70°C                                    |       | V |     |      | 1310        | 1310 | 30KM     | 0~70°C   | V   | 1        |
| Single Mode | SFPLHX30D-w      | [SFPLHX30D-w] SFP-100LHX, 1.25Gbps, 1310nm, Single-mode, 30km, -40~85°C, LC with DDM function            |       | V |     |      | 1310        | 1310 | 30KM     | -40~85°C | V   | 1        |
| Single Mode | SFP100SM40B13    | [SFP100SM40B13] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 40Km, LC, Temp. -10°C~70°C                | V     |   |     | V    | 1310        | 1550 | 40KM     | -10~70°C |     | 1        |
| Single Mode | SFP100SM40B15    | [SFP100SM40B15] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 40Km, LC, Temp. -10°C~70°C                | V     |   |     | V    | 1550        | 1310 | 40KM     | -10~70°C |     | 1        |
| Single Mode | SFP100SM40B13-w  | [SFP100SM40B13-w] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 40Km, LC, Temp. -40°C~85°C              | V     |   |     | V    | 1310        | 1550 | 40KM     | -40~85°C |     | 1        |
| Single Mode | SFP100SM40B15-w  | [SFP100SM40B15-w] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 40Km, LC, Temp. -40°C~85°C              | V     |   |     | V    | 1550        | 1310 | 40KM     | -40~85°C |     | 1        |
| Single Mode | SFP100SM40B13D   | [SFP100SM40B13D] 100Mbps BIDI DDM single-mode transceiver 1310nm 40km                                    | V     |   |     | V    | 1310        | 1550 | 40KM     | -10~70°C | V   | 1        |
| Single Mode | SFP100SM40B15D   | [SFP100SM40B15D] 100Mbps BIDI DDM single-mode transceiver 1550nm 40km                                    | V     |   |     | V    | 1550        | 1310 | 40KM     | -10~70°C | V   | 1        |

|             |                  |   |   |   |   |      |      |       |          |   |   |
|-------------|------------------|---|---|---|---|------|------|-------|----------|---|---|
| Single Mode | SFP100SM40B13D-w | [SFP100SM40B13D-w] 100Mbps BIDI DDM single-mode transceiver 1310nm 40km, -40°C~85°C                 | V |   | V | 1310 | 1550 | 40KM  | -40~85°C | V | 1 |
| Single Mode | SFP100SM40B15D-w | [SFP100SM40B15D-w] 100Mbps BIDI DDM single-mode transceiver 1550nm 40km, -40°C~85°C                 | V |   | V | 1550 | 1310 | 40KM  | -40~85°C | V | 1 |
| Single Mode | SFPLGX40B13      | [SFPLGX40B13] 1000Base-LX, 1.25Gbps, Single-Mode 1310nm, 40km, -10°C~70°C                           | V |   | V | 1310 | 1310 | 40KM  | 0~70°C   |   | 1 |
| Single Mode | SFPLGX40B15      | [SFPLGX40B15] 1000Base-LX, S.M., BIDI TX 1310/RX 1550nm, 40Km, LC, Temp. -10°C~70°C                 | V |   | V | 1310 | 1550 | 40KM  | -10~70°C |   | 1 |
| Single Mode | SFPLGX40B15      | [SFPLGX40B15] 1000Base-LX, S.M., BIDI TX 1550/RX 1310nm, 40Km, LC, Temp. -10°C~70°C                 | V |   | V | 1550 | 1310 | 40KM  | -10~70°C |   | 1 |
| Single Mode | SFPLGX40B13-w    | [SFPLGX40B13-w] 1000Base-LX, S.M., BIDI TX 1310/RX 1550nm, 40Km, LC, Temp. -40°C~85°C               | V |   | V | 1310 | 1550 | 40KM  | -40~85°C |   | 1 |
| Single Mode | SFPLGX40B15-w    | [SFPLGX40B15-w] 1000Base-LX, S.M., BIDI TX 1550/RX 1310nm, 40Km, LC, Temp. -40°C~85°C               | V |   | V | 1550 | 1310 | 40KM  | -40~85°C |   | 1 |
| Single Mode | SFPLGX40B13D-w   | [SFPLGX40B13D-w] 1000Base-LX, S.M., BIDI DDM TX 1310/RX 1550nm, 40Km, LC, Temp. -40°C~85°C          | V |   | V | 1310 | 1550 | 40KM  | -40~85°C | V | 1 |
| Single Mode | SFPLGX40B15D-w   | [SFPLGX40B15D-w] 1000Base-LX, S.M., BIDI DDM TX 1550/RX 1310nm, 40Km, LC, Temp. -40°C~85°C          | V |   | V | 1550 | 1310 | 40KM  | -40~85°C | V | 1 |
| Single Mode | SFP10GER40D      | [SFP10GER40D] Single-mode 10Gbps 40KM Fiber Transceiver with DDM, LC, Operating Temp. -10~70°C      |   | V |   | 1550 | 1550 | 80KM  | -10~70°C | V | 1 |
| Single Mode | SFPGXD50         | [SFPGXD50] 1000Base-XD Single-mode Transceiver 50km, LC, Operating Temp. -10~70°C                   | V |   | V | 1550 | 1550 | 50KM  | -10~70°C |   | 1 |
| Single Mode | SFPGXD50-w       | [SFPGXD50-w] 1000Base-XD Single-mode Transceiver 50km, LC, Operating Temp. -40~85°C                 | V |   | V | 1550 | 1550 | 50KM  | -40~85°C |   | 1 |
| Single Mode | SFPGXD50D        | [SFPGXD50D] 1000Base XD DDM single-mode transceiver 50km, -10°C~70°C                                | V |   | V | 1550 | 1550 | 50KM  | -10~70°C | V | 1 |
| Single Mode | SFPGXD50D-w      | [SFPGXD50D-w] SFP-1000XD-DD-IT, 1.25Gbps, 1550nm, Single-mode, 50km, -40~85°C, LC with DDM function | V |   | V | 1550 | 1550 | 50KM  | -40~85°C | V | 1 |
| Single Mode | SFP100SM60       | [SFP100SM60] SFP Transceiver, 100Mbps, Single mode 60Km, LC, Temp. -10°C~70°C                       | V |   | V | 1310 | 1310 | 60KM  | -10~70°C |   | 1 |
| Single Mode | SFP100SM60-w     | [SFP100SM60-w] SFP Transceiver, 100Mbps, Single mode 60Km, LC, Temp. -40°C~85°C                     | V |   | V | 1310 | 1310 | 60KM  | -40~85°C |   | 1 |
| Single Mode | SFP100SM60D      | [SFP100SM60D] Single-mode 100Mbps 60KM Fiber Transceiver with DDM, LC, Operating Temp. -10~70°C     | V |   | V | 1310 | 1310 | 60KM  | -10~70°C | V | 1 |
| Single Mode | SFP100SM60D-w    | [SFP100SM60D-w] Single-mode 100Mbps 60KM Fiber Transceiver with DDM, LC, Operating Temp. -40~85°C   | V |   | V | 1310 | 1310 | 60KM  | -40~85°C | V | 1 |
| Single Mode | SFP100SM60B13    | [SFP100SM60B13] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 60Km, LC, Temp. -10°C~70°C           | V |   | V | 1310 | 1550 | 60KM  | -10~70°C |   | 1 |
| Single Mode | SFP100SM60B15    | [SFP100SM60B15] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 60Km, LC, Temp. -10°C~70°C           | V |   | V | 1550 | 1310 | 60KM  | -10~70°C |   | 1 |
| Single Mode | SFP100SM60B13-w  | [SFP100SM60B13-w] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 60Km, LC, Temp. -40°C~85°C         | V |   | V | 1310 | 1550 | 60KM  | -40~85°C |   | 1 |
| Single Mode | SFP100SM60B15-w  | [SFP100SM60B15-w] SFP Transceiver, 100Mbps, Single mode BIDI/WDM 60Km, LC, Temp. -40°C~85°C         | V |   | V | 1550 | 1310 | 60KM  | -40~85°C |   | 1 |
| Single Mode | SFP100SM60B13D-w | [SFP100SM60B13D-w] 100Mbps BIDI DDM single-mode transceiver 1310nm 60km, -40°C~85°C                 | V |   | V | 1310 | 1550 | 60KM  | -40~85°C | V | 1 |
| Single Mode | SFP100SM60B15D-w | [SFP100SM60B15D-w] 100Mbps BIDI DDM single-mode transceiver 1550nm 60km, -40°C~85°C                 | V |   | V | 1550 | 1310 | 60KM  | -40~85°C | V | 1 |
| Single Mode | SFPLX60B13       | [SFPLX60B13] 1000Base-LX, S.M., BIDI TX 1310/RX 1550nm, 60Km, LC, Temp. -10°C~70°C                  | V |   | V | 1310 | 1550 | 60KM  | -10~70°C |   | 1 |
| Single Mode | SFPLX60B15       | [SFPLX60B15] 1000Base-LX, S.M., BIDI TX 1550/RX 1310nm, 60Km, LC, Temp. -10°C~70°C                  | V |   | V | 1550 | 1310 | 60KM  | -10~70°C |   | 1 |
| Single Mode | SFPLX60B13-w     | [SFPLX60B13-w] 1000Base-LX, S.M., BIDI TX 1310/RX 1550nm, 60Km, LC, Temp. -40°C~85°C                | V |   | V | 1310 | 1550 | 60KM  | -40~85°C |   | 1 |
| Single Mode | SFPLX60B15-w     | [SFPLX60B15-w] 1000Base-LX, S.M., BIDI TX 1550/RX 1310nm, 60Km, LC, Temp. -40°C~85°C                | V |   | V | 1550 | 1310 | 60KM  | -40~85°C |   | 1 |
| Single Mode | SFPLX60B13D      | [SFPLX60B13D] 1000Base-LX, S.M., BIDI DDM TX 1310/RX 1550nm, 60Km, LC, Temp. -10°C~70°C             | V |   | V | 1310 | 1550 | 60KM  | -10~70°C | V | 1 |
| Single Mode | SFPLX60B15D      | [SFPLX60B15D] 1000Base-LX, S.M., BIDI DDM TX 1550/RX 1310nm, 60Km, LC, Temp. -10°C~70°C             | V |   | V | 1550 | 1310 | 60KM  | -10~70°C | V | 1 |
| Single Mode | SFPLX60B13D-w    | [SFPLX60B13D-w] 1000Base-LX, S.M., BIDI DDM TX 1310/RX 1550nm, 60Km, LC, Temp. -40°C~85°C           | V |   | V | 1310 | 1550 | 60KM  | -40~85°C | V | 1 |
| Single Mode | SFPLX60B15D-w    | [SFPLX60B15D-w] 1000Base-LX, S.M., BIDI DDM TX 1550/RX 1310nm, 60Km, LC, Temp. -40°C~85°C           | V |   | V | 1550 | 1310 | 60KM  | -40~85°C | V | 1 |
| Single Mode | SFPGZX70         | [SFPGZX70] 1000Base-ZX Single-mode Transceiver 70km, LC, Operating Temp. -10~70°C                   | V |   | V | 1550 | 1550 | 70KM  | -10~70°C |   | 1 |
| Single Mode | SFPGZX70-w       | [SFPGZX70-w] 1000Base-ZX Single-mode Transceiver 70km, LC, Operating Temp. -40~85°C                 | V |   | V | 1550 | 1550 | 70KM  | -40~85°C |   | 1 |
| Single Mode | SFPGZX70D        | [SFPGZX70D] SFP-1000ZX-DD-IT, 1.25Gbps, 1550nm, Single-mode, 70km, 0~70°C, LC with DDM function     | V |   | V | 1550 | 1550 | 70KM  | 0~70°C   | V | 1 |
| Single Mode | SFPGZX70D-w      | [SFPGZX70D-w] SFP-1000ZX-DD-IT, 1.25Gbps, 1550nm, Single-mode, 70km, -40~85°C, LC with DDM function | V |   | V | 1550 | 1550 | 70KM  | -40~85°C | V | 1 |
| Single Mode | SFP100SM80       | [SFP100SM80] SFP Transceiver, 100Mbps, Single mode 80Km, LC, Temp. -10°C~70°C                       | V |   | V | 1310 | 1310 | 80KM  | -10~70°C |   | 1 |
| Single Mode | SFP100SM80-w     | [SFP100SM80-w] SFP Transceiver, 100Mbps, Single mode 80Km, LC, Temp. -40°C~85°C                     | V |   | V | 1310 | 1310 | 80KM  | -40~85°C |   | 1 |
| Single Mode | SFPGZX80         | [SFPGZX80] SFP-1000ZX, 1.25Gbps, Single-Mode 1550nm, 80km, -10°C~70°C                               | V |   | V | 1550 | 1550 | 80KM  | 0~70°C   |   | 1 |
| Single Mode | SFP10GZR80D      | [SFP10GZR80D] Single-mode 10Gbps 80KM Fiber Transceiver with DDM, LC, Operating Temp. -10~70°C      |   | V | V | 1550 | 1550 | 80KM  | -10~70°C | V | 1 |
| Single Mode | SFP100SM100      | [SFP100SM100] SFP Transceiver, 100Mbps, Single mode 100Km, LC, Temp. -10°C~70°C                     | V |   | V | 1550 | 1550 | 100KM | -10~70°C |   | 1 |
| Single Mode | SFP100SM100-w    | [SFP100SM100-w] SFP Transceiver, 100Mbps, Single mode 100Km, LC, Temp. -40°C~85°C                   | V |   | V | 1550 | 1550 | 100KM | -40~85°C |   | 1 |
| Single Mode | SFPGZX110        | [SFPGZX110] SFP-1000EZ, 1.25Gbps, 1550nm, Single-Mode, 110km, 0~70°C                                | V |   | V | 1550 | 1550 | 110KM | 0~70°C   |   | 1 |
| Single Mode | SFPGZX110-w      | [SFPGZX110-w] SFP-1000EZ, 1.25Gbps, 1550nm, Single-Mode, 110km, -40~85°C                            | V |   | V | 1550 | 1550 | 110KM | -40~85°C |   | 1 |
| Single Mode | SFP100SM120      | [SFP100SM120] SFP Transceiver, 100Mbps, Single mode 120Km, LC, Temp. -10°C~70°C                     | V |   | V | 1550 | 1550 | 120KM | -10~70°C |   | 1 |
| Single Mode | SFP100SM120-w    | [SFP100SM120-w] SFP Transceiver, 100Mbps, Single mode 120Km, LC, Temp. -40°C~85°C                   | V |   | V | 1550 | 1550 | 120KM | -40~85°C |   | 1 |
| Single Mode | SFPGZX120        | [SFPGZX120] SFP-1000EZ, 1.25Gbps, 1550nm, Single-Mode, 120km, 0~70°C                                | V |   | V | 1550 | 1550 | 120KM | 0~70°C   |   | 1 |
| Single Mode | SFPGZX120-w      | [SFPGZX120-w] SFP-1000EZ, 1.25Gbps, 1550nm, Single-Mode, 120km, -40~85°C                            | V |   | V | 1550 | 1550 | 120KM | -40~85°C |   | 1 |
| Single Mode | SFPGZX120D       | [SFPGZX120D] SFP-1000EZ, 1.25Gbps, DDM, 1550nm, Single-Mode, 120km, 0~70°C                          | V |   | V | 1550 | 1550 | 120KM | 0~70°C   | V | 1 |
| Single Mode | SFPGZX120D-w     | [SFPGZX120D-w] SFP-1000EZ, 1.25Gbps, DDM, 1550nm, Single-Mode, 120km, -40~85°C                      | V |   | V | 1550 | 1550 | 120KM | -40~85°C | V | 1 |
| Copper SFP  | SFPGRJ45         | [SFPGRJ45] Copper SFP, 1.25 Gigabit, 10/100/1000T, RJ-45 Connector, Temp. 0°C~70°C                  | V |   |   | -    | -    | 100M  | 0~70°C   |   | 1 |
| Copper SFP  | SFPGRJ45-w       | [SFPGRJ45-w] Copper SFP, 1.25 Gigabit, 10/100/1000T, RJ-45 Connector, Temp. -40~85°C                | V |   |   | -    | -    | 100M  | -40~85°C |   | 1 |

\*If there is any required SFP not available in above list, please feel free to contact Korenix. We will do our best to help you.